

Plasmaterials, Inc.
 2268 Research Drive
 Livermore, CA 94550
 Ph: (925) 447-4030 Fx: (925) 447-4031
<http://plasmaterials.com>

MATERIAL SAFETY DATA SHEET

Section 1- PRODUCT IDENTIFICATION

COMPOSITION Zr	PRODUCT NAME Zirconium
--------------------------	----------------------------------

Section 2- HAZARDOUS INGREDIENTS

Note: Products under normal conditions do not represent an inhalation, ingestion or contact health hazard.

MATERIAL OR COMPONENT	CAS NUMBER	WT%	EXPOSURE LIMITS	
			OSHA PEL (Mg/M3)	ACGIH TLV(MG/M3)
Zirconium	7440-67-7	100%	5mg/m³	5mg/m³

Section 3- PHYSICAL DATA

MATERIAL IS (AT NORMAL CONDITIONS) <input type="checkbox"/> Liquid <input type="checkbox"/> Solid <input type="checkbox"/> Gas <input type="checkbox"/> Other	APPEARANCE AND ODOR Grayish-white lustrous metal
MELTING POINT (BASE METAL) 1852°C	SPECIFIC GRAVITY 6.506gm/cc at 20

Section 4- FIRE AND EXPLOSION

Flash Point (Method Used) N/A	Flammable Limits Flammable	LEL N/D	UEL N/D
-----------------------------------------	--------------------------------------	-------------------	-------------------

EXTINGUISHING MEDIA

DO NOT USE WATER ON METAL FIRES. Use dry chemical, CO2, sand and graphite.

SPECIAL FIRED FIGHTING PROCEDURES

Wear a self-contained breathing apparatus & full protective clothing to prevent contact with skin & eyes.

UNUSUAL FIRE AND EXPLOSION HAZARDS

See Attached

Section 5- REACTIVITY DATA

STABILITY Unstable (moisture, friction & oxidants are contributors to instability)	INCOMPATABILITY (MATERIALS TO AVOID) CO2, N2, CC14, nitryl fluoride, oxygen containing compounds, P and water
CONDITIONS TO AVOID See Attached	

HAZARDOUS DECOMPOSITION PRODUCTS

Zirconium Oxide

Section 6- HEALTH HAZARD GUIDE

MAJOR EXPOSURE HAZARD

Inhalation **Skin** **Skin Absorption** **Eye Contact** **Ingestion**

EFFECTS OF OVEREXPOSURE

INHALATION: Respiratory irritant. Sneezing, coughing, difficulty breathing, headache & bronchitis.

SKIN CONTACT: Irritating, redness, inflammation possible.

EYE CONTACT: Irritating, redness, watering & inflammation possible.

OTHER: Zirconium and its salts generally have low systemic toxicity. Zirconium is not an important industrial poison. Most zirconium compounds in common uses are insoluble and are considered inert. Pulmonary granuloma in zirconium workers has been reported.

EMERGENCY & FIRST AID PROCEDURES

INHALATION: Remove to fresh air; give oxygen if breathing is difficult. Seek medical attention.

SKIN CONTACT: Brush off skin and wash area with soap and water. Seek medical attention.

EYE CONTACT: Flush eyes with lukewarm water for 15 minutes. Seek medical attention.

INGESTION: Give 1-2 cups of milk or water and induce vomiting. Seek medical attention.

Section 7- SPILL OR LEAK PROCEDURES

SPILL OR LEAK PROCEDURES

See Attached

WASTE DISPOSAL METHODS

Observe all federal, state and local regulations when storing or disposing of this substance.

Section 8- SPECIAL PROTECTION

RESPIRATORY

Wear NIOSH- approved dust-mist-fume cartridge respirator.

VENTILATION

Provide local exhaust ventilation. Maintain exposure below TLV. Mechanical ventilation not recommended. Handle in dry, inert atmosphere.

EYE PROTECTION & PROTECTIVE CLOTHING

Wear neoprene protective gloves. Wear safety glasses and wear protective clothing to prevent contamination of skin and clothes.

Section 9- SPECIAL PRECAUTIONS

Store in tightly closed containers in a cool, dry place. Wash hands and face thoroughly after handling and before meals.

The information in this MSDS was obtained from sources, which we believe are reliable. However, the information is provided without any representation or warranty, express or implied, regarding the accuracy or correctness.

The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.

Zirconium Continued

Unusual Fire and Explosion Hazards:

Material may emit toxic fumes if involved in fire. Dangerous fire hazard, in the form of dust, when exposed to heat or flame or by chemical reaction with oxidizers. Dangerous explosion hazard in the form of dust by chemical reaction with alkali hydroxides, air, alkali metal chromates, dichromate, molybdates, salts, sulfides, tungstates, borax, C14, CuO, Pb, P, KClO₃, KNO₃, nitryl fluoride. Explosive range = 0.16 g/l in air. Powder damp with 5-10% of water may ignite and although 25% of water is regarded as a safe concentration, ignition of a 50% paste on breakage of a glass container has been observed. Although water is used to prevent ignition, the powder, once ignited, will burn under water (88.8% oxygen) more violently than in air (21% oxygen). The affinity of zirconium for oxygen is great, particularly when the metal is finely divided.

Conditions to Avoid:

1. Exclusion of air or oxygen by use of inert gases.
2. Exclusion of water, its vapor and other contaminants or oxidants.
3. Control of particle size.
4. Limitation of amount of powder handled or exposed.
5. Limitation of exposure of personnel.

AVOID: water, heat, sparks, flame, friction or oxidizers.

Spill or Leak Procedures:

Wear a self-contained breathing apparatus and full protective clothing. Isolate the area where the spill occurred. Insure proper ventilation and water/moisture are kept out of area. Vacuum up the spill using a high efficiency unit then place in a container for proper disposal. Take care not to raise dust.